

1

# FOUNDATION FOR INTELLIGENT PHYSICAL AGENTS

2

3

4

5

## FIPA ACL Message Representation in 6 Bit-Efficient Encoding Specification

7

<b>Document title</b>	FIPA ACL Message Representation in Bit-Efficient Encoding Specification		
<b>Document number</b>	XC00069E	<b>Document source</b>	FIPA Agent Management
<b>Document status</b>	Experimental	<b>Date of this status</b>	2001/08/10
<b>Supersedes</b>	FIPA00024		
<b>Contact</b>	fab@fipa.org		
<b>Change history</b>			
2000/07/25	Approved for Experimental		
2001/06/25	Added clarification about code table usage; added grammar rule for "hour"; removed unnecessary superscripts from ExprStart rule		
2001/08/10	Line numbering added		

8

9

10

11

12

13

14

15

16 © 2000 Foundation for Intelligent Physical Agents - <http://www.fipa.org/>

17 Geneva, Switzerland

### Notice

Use of the technologies described in this specification may infringe patents, copyrights or other intellectual property rights of FIPA Members and non-members. Nothing in this specification should be construed as granting permission to use any of the technologies described. Anyone planning to make use of technology covered by the intellectual property rights of others should first obtain permission from the holder(s) of the rights. FIPA strongly encourages anyone implementing any part of this specification to determine first whether part(s) sought to be implemented are covered by the intellectual property of others, and, if so, to obtain appropriate licenses or other permission from the holder(s) of such intellectual property prior to implementation. This specification is subject to change without notice. Neither FIPA nor any of its Members accept any responsibility whatsoever for damages or liability, direct or consequential, which may result from the use of this specification.

18 **Foreword**

19 The Foundation for Intelligent Physical Agents (FIPA) is an international organization that is dedicated to promoting the  
20 industry of intelligent agents by openly developing specifications supporting interoperability among agents and agent-  
21 based applications. This occurs through open collaboration among its member organizations, which are companies and  
22 universities that are active in the field of agents. FIPA makes the results of its activities available to all interested parties  
23 and intends to contribute its results to the appropriate formal standards bodies.

24 The members of FIPA are individually and collectively committed to open competition in the development of agent-  
25 based applications, services and equipment. Membership in FIPA is open to any corporation and individual firm,  
26 partnership, governmental body or international organization without restriction. In particular, members are not bound to  
27 implement or use specific agent-based standards, recommendations and FIPA specifications by virtue of their  
28 participation in FIPA.

29 The FIPA specifications are developed through direct involvement of the FIPA membership. The status of a  
30 specification can be either Preliminary, Experimental, Standard, Deprecated or Obsolete. More detail about the process  
31 of specification may be found in the FIPA Procedures for Technical Work. A complete overview of the FIPA  
32 specifications and their current status may be found in the FIPA List of Specifications. A list of terms and abbreviations  
33 used in the FIPA specifications may be found in the FIPA Glossary.

34 FIPA is a non-profit association registered in Geneva, Switzerland. As of January 2000, the 56 members of FIPA  
35 represented 17 countries worldwide. Further information about FIPA as an organization, membership information, FIPA  
36 specifications and upcoming meetings may be found at <http://www.fipa.org/>.

37    **Contents**

38	1	Scope .....	1
39	2	Bit-Efficient ACL Representation .....	2
40	2.1	Component Name .....	2
41	2.2	Syntax .....	2
42	2.3	Using Dynamic Code Tables .....	5
43	2.4	Notes on the Grammar Rules .....	7
44	3	References .....	9
45			

45    **1 Scope**

46    This document is part of the FIPA specifications and deals with message transportation between inter-operating agents.  
47    This document also forms part of the FIPA Agent Management Specification [FIPA00023] and contains specifications  
48    for:

49              Syntactic representation of ACL in a bit-efficient form.

51

## 2 Bit-Efficient ACL Representation

This section defines the message transport syntax for a bit-efficient encoding which is expressed in standard EBNF format (see *Table 1*).

Note that this representation is not compatible with [FIPA00075].

Grammar rule component	Example
Terminal tokens are enclosed in double quotes	" ( "
Non-terminals are written as capitalised identifiers	Expression
Square brackets denote an optional construct	[ " , " OptionalArg ]
Vertical bars denote an alternative between choices	Integer   Float
Asterisk denotes zero or more repetitions of the preceding expression	Digit*
Plus denotes one or more repetitions of the preceding expression	Alpha+
Parentheses are used to group expansions	( A   B )*
Productions are written with the non-terminal name on the left-hand side, expansion on the right-hand side and terminated by a full stop	ANonTerminal = "terminal".
0x?? is a hexadecimal byte	0x00

**Table 1:** EBNF Rules

White space is not allowed between tokens.

## 2.1 Component Name

The name assigned to this component is:

fipa.acl.rep.bitefficient.std

## 2.2 Syntax

```
ACLCommunicativeAct      = Message.

Message                  = Header MessageType MessageParameter* EndofMsg.

Header                   = MessageId Version.

MessageId                = 0xFA
                           | 0xFB
                           | 0xFC.                                /* see comment 1 below */

Version                 = Byte.                               /* see comment 2 below */

EndofMsg                 = EndOfCollection.

EndOfCollection          = 0x01.

MessageType              = PredefinedMsgType
                           | UserDefinedMsgType.               /* see comment 3 below */

UserDefinedMsgType       = 0x00 MsgTypeName.

MsgTypeName               = BinWord.

MessageParameter          = PredefinedParam
                           | UserDefinedMsgParam.            /* see comment 4 below */

UserDefinedMsgParam      = 0x00 ParameterName ParameterValue.
```

```

94
95 ParameterName          = BinWord.
96
97 ParamterValue          = BinExpression.
98
99 PredefinedMsgType      = 0x01           /* accept-proposal */
100   | 0x02           /* agree */
101   | 0x03           /* cancel */
102   | 0x04           /* cfp */
103   | 0x05           /* confirm */
104   | 0x06           /* disconfirm */
105   | 0x07           /* failure */
106   | 0x08           /* inform */
107   | 0x09           /* inform-if */
108   | 0x0a           /* inform-ref */
109   | 0x0b           /* not-understood */
110   | 0x0c           /* propagate */
111   | 0x0d           /* propose */
112   | 0x0e           /* proxy */
113   | 0x0f           /* query-if */
114   | 0x10           /* query-ref */
115   | 0x11           /* refuse */
116   | 0x12           /* reject-proposal */
117   | 0x13           /* request */
118   | 0x14           /* request-when */
119   | 0x15           /* request-whenever */
120   | 0x16           /* subscribe */
121
122 PredefinedMsgParam     = 0x02 AgentIdentifier /* :sender */
123   | 0x03 RecipientExpr    /* :receiver */
124   | 0x04 MsgContent       /* :content */
125   | 0x05 ReplyWithParam   /* :reply-with */
126   | 0x06 ReplyByParam     /* :reply-by */
127   | 0x07 InReplyToParam   /* :in-reply-to */
128   | 0x08 ReplyToParam     /* :reply-to */
129   | 0x09 Language         /* :language */
130   | 0x0a Encoding          /* :encoding */
131   | 0x0b Ontology          /* :ontology */
132   | 0x0c Protocol          /* :protocol */
133   | 0x0d ConversationID. /* :conversation-id */
134
135 AgentIdentifier        = 0x02 AgentName
136   [Addresses]
137   [Resolvers]
138   (UserDefinedParameter)*
139   EndOfCollection.
140
141 AgentName               = BinWord.
142
143 Addresses               = 0x02 UrlCollection.
144
145 Resolvers               = 0x03 AgentIdentifierCollection.
146
147 UserDefinedParameter    = 0x04 BinWord BinExpression.
148
149 UrlCollection           = (Url)* EndofCollection.
150
151 Url                     = BinWord.
152
153 AgentIdentifierCollection = (AgentIdentifier)* EndOfCollection.
154
155 RecipientExpr           = AgentIdentifierCollection.
156
157

```

```

158 MsgContent           = BinExpression.
159
160 ReplyWithParam      = BinExpression.
161
162 ReplyByParam        = BinDateTimeToken.
163
164 InReplyToParam      = BinExpression.
165
166 ReplyToParam        = RecipientExpr.
167
168 Language             = BinExpression.
169
170 Encoding             = BinExpression.
171
172 Ontology             = BinExpression.
173
174 Protocol             = BinWord.
175
176 ConversationID      = BinExpression.
177
178 BinWord              = 0x10 Word 0x00
179 | 0x11 Index.
180
181 BinNumber            = 0x12 Digits          /* Decimal Number */
182 | 0x13 Digits.        /* Hexadecimal Number */
183
184 Digits               = CodedNumber+.
185
186 BinString             = 0x14 String 0x00    /* New string literal */
187 | 0x15 Index.         /* String literal from code table*/
188 | 0x16 Len8 ByteSeq.  /* New ByteLengthEncoded string */
189 | 0x17 Len16 ByteSeq. /* New ByteLengthEncoded string */
190 | 0x18 Index.         /* ByteLengthEncoded from code table*/
191 | 0x19 Len32 ByteSeq. /* New ByteLengthEncoded string */
192
193 BinDateTimeToken      = 0x20 BinDate
194 | 0x21 BinDate TypeDesignator.
195
196 BinDate               = Year Month Day Hour Minute Second Millisecond.
197 | /* see comment 9 below */
198
199 BinExpression          = BinExpr
200 | 0xFF BinString.     /* See comment 10 below */
201
202 BinExpr                = BinWord
203 | BinString
204 | BinNumber
205 | ExprStart BinExpr* ExprEnd.
206
207 ExprStart              = 0x60          /* Level down (i.e. '(' -character) */
208 | 0x70 Word 0x00       /* Level down, new word follows */
209 | 0x71 Index           /* Level down, word code follows */
210 | 0x72 Digits          /* Level down, number follows */
211 | 0x73 Digits          /* Level down, hex number follows */
212 | 0x74 String 0x00     /* Level down, new string follows */
213 | 0x75 Index           /* Level down, string code follows */
214 | 0x76 Len8 String.    /* Level down, new byte string (1 byte) */
215 | 0x77 Len16 String.   /* Level down, new byte string (2 byte) */
216 | 0x78 Len32 String.   /* Level down, new byte string (4 byte) */
217 | 0x79 Index.          /* Level down, byte string code follows */
218
219 ExprEnd                = 0x40          /* Level up (i.e. ')' -character) */
220 | 0x50 Word 0x00       /* Level up, new word follows */
221 | 0x51 Index.          /* Level up, word code follows */

```

```

222          | 0x52 Digits      /* Level up, number follows */
223          | 0x53 Digits      /* Level up, hexadecimal number follows */
224          | 0x54 String 0x00 /* Level up, new string follows */
225          | 0x55 Index       /* Level up, string code follows */
226          | 0x56 Len8 String /* Level up, new byte string (1 byte) */
227          | 0x57 Len16 String/* Level up, new byte string (2 byte) */
228          | 0x58 Len32 String/* Level up, new byte string (4 byte) */
229          | 0x59 Index.      /* Level up, byte string code follows */

230
231 ByteSeq        = Byte*.

232
233 Index          = Byte
234 | Short.        /* See comment 7 below */

235
236 Len8           = Byte.          /* See comment 8 below */

237
238 Len16          = Short.        /* See comment 8 below */

239
240 Len32          = Long.         /* See comment 8 below */

241
242 Year            = Byte Byte.

243
244 Month           = Byte.

245
246 Day             = Byte.

247
248 Hour            = Byte.

249
250 Minute          = Byte.

251
252 Second          = Byte.

253
254 Millisecond     = Byte Byte.

255
256 Word             = /* as in [FIPA00070] */

257
258 String           = /* as in [FIPA00070] */

259
260 CodedNumber      = /* See comment 5 below */

261
262 TypeDesignator   = /* as in [FIPA00070] */

263

```

## 2.3 Using Dynamic Code Tables

The transport syntax can be used with or without dynamic code table. Using dynamic code tables is an optional feature, which gives more compact output but might not be appropriate if communicating peers does not have sufficient memory (for example, in case of low-end PDAs or smart phones).

To use dynamic code tables the encoder inserts new entries (for example, Word, String, etc.) into a code table while constructing bit-efficient representation for ACL message. The code table is initially empty and whenever a new entry is added to the code table, the smallest available code number is allocated to it. There is no need to transfer these index codes explicitly over the communication channel. Once the code table becomes full and a new code needs to be added, the sender first removes  $\text{size} \gg 3^1$  entries from the code table using a Least Recently Used (LRU) algorithm and then adds a new entry to code table. For example, should the code table size be 512 entries, 64 entries are removed. Correspondingly the decoder removes entries from the code table when it receives a new entry from the encoder.

The size of the code table, if used, is between 256 ( $2^8$ ) and 65536 ( $2^{16}$ ) entries. The output of this code table is always one or two bytes (one byte only when the code table size is  $2^8$ ). Using two-byte output code wastes some bits, but

---

<sup>1</sup> Right shifted by 3 bit positions – approximately 10%.

279 allows for much faster parsing of messages. The code table is unidirectional, that is, if sender A adds something to the  
280 code table when sending a message to B, then B cannot use this code table entry when sending a message back to A.  
281

282 Both peers must agree the code table size before its usage; this process is not part of this specification. Furthermore,  
283 having more compact output, one code table should be applied to more than one message; the method of mapping  
284 messages to appropriate code table is not part of this specification.

285

286

## 286 2.4 Notes on the Grammar Rules

- 287 1. The first byte defines the message identifier. The identifier byte can be used to separate bit-efficient ACL messages  
 288 from (for example) string-based messages and separate different coding schemes. The value 0xFA defines a bit-  
 289 efficient coding scheme without dynamic code tables and the value 0xFB defines a bit-efficient coding scheme with  
 290 dynamic code tables. The message identifier 0xFC is used when dynamic code tables are being used, but the  
 291 sender does not want to update code tables (even if message contains strings that should be added to code table).  
 292
- 293 2. The second byte defines the version number. The version number byte contains the major version number in the  
 294 upper four bits and minor version number in the lower four bits. This specification defines version 1.0 (coded as  
 295 0x10).
- 296 3. All message types defined in this specification have a predefined code. If an encoder sends an ACL message with  
 297 a message type which has no predefined code, it must use the extension mechanism which adds a new message  
 298 type into code table (if code tables are being used).
- 299 4. All message parameters defined in this specification have a predefined code. If a message contains a user defined  
 300 message parameter, an extension mechanism is used (byte 0x00) and new entry is added to code table (if code  
 301 table is used).
- 302 5. Numbers are coded by reserving four bits for each digit in the number's ASCII representation, that is, two ASCII  
 303 numbers are coded into one byte. *Table 1* shows a 4-bit code for each number and special codes that may appear  
 304 in ASCII coded numbers.

305 If the ASCII presentation of a number contains odd number characters, the last four bits of the coded number are  
 306 set to zero (the Padding token), otherwise an additional 0x00 byte is added to end of coded number. If the  
 307 number to be coded is integer, decimal number, or octal number, the identifier byte 0x12 is used. For hexadecimal  
 308 numbers, the identifier byte 0x13 is used. Hexadecimal numbers are converted to integers before coding (the  
 309 coding scheme does not allow characters from a through f to appear in number form).

310 315 Numbers are never added to a dynamic code table.  
 316  
 317

Token	Code	Token	Code
Padding	0000	7	1000
0	0001	8	1001
1	0010	9	1010
2	0011	+	1100
3	0100	E	1101
4	0101	-	1110
5	0110	.	1111
6	0111		

318 319 6. **Table 1:** Binary Representation of Number Tokens

- 320 321 7. Index is a pointer to code table entry and its size (in bits) depends on the code table size. If the code table size is  
 322 256 entries, the size of the index is one byte; otherwise its size is two bytes (represented in network byte order).  
 323
- 324 8. Byte is a one-byte code word, Short is a short integer (two bytes, network byte order) and Long is a long integer  
 325 (four bytes, network byte order).  
 326

- 327 9. Dates are coded as numbers, that is, four bits are reserved for each ASCII number (see comment 5 above).  
328 Information whether the type designator is present or not, is coded into identifier byte. These fields always have  
329 static length (two bytes for year and milliseconds, one byte for other components).  
330
- 331 10. None of the actual content of the message (the information contained in the :content parameter of the ACL  
332 message) is coded nor are any of its components are added to a code table.  
333
- 334

**334    3 References**

- 335 [FIPA00023] FIPA Agent Management Specification. Foundation for Intelligent Physical Agents, 2000.  
336 <http://www.fipa.org/specs/fipa00023/>
- 337 [FIPA00067] FIPA Agent Message Transport Service Specification. Foundation for Intelligent Physical Agents, 2000.  
338 <http://www.fipa.org/specs/fipa00067/>
- 339 [FIPA00070] FIPA ACL Message Representation in String Specification. Foundation for Intelligent Physical Agents, 2000.  
340 <http://www.fipa.org/specs/fipa00070/>
- 341 [FIPA00075] FIPA Agent Message Transport Protocol for IIOP Specification. Foundation for Intelligent Physical Agents, 2000.  
342 <http://www.fipa.org/specs/fipa00075/>
- 343
- 344